

Solar Panel

User Guide


Model: PV350D

Contact Us:
www.bluettipower.com
service@bluettipower.com




User Guide


What is in the box



Solar Panel






MC4 Cable






User Manual &
Warranty Card

How to use


1 Unfold



2 Adjust the kickstand




3 Connect to power station




MC4 Connectors

Solar Charging Cable

Multi-functional
Aviation Cable
(XT90 -Aviation)



AC200MAX



User Guide

Note:

Whether connected in series or parallel, make sure the total voltage of solar panels is under the power station's input voltage limit.

Attention

Regular inspection and maintenance are required to prolong the lifespan of solar panels.



No fall



No soak



No bend



No shading



No scratch

Warning:

Do not use solar panels in extreme weather conditions like thunderstorms, floods, typhoons, etc.

Always use solar panels within the specified temperature range (14-149°F/-10-65°C).

Technical details

PV350D		
Maximum Power(Pm)	350W*	
Solar Cell Lamination	ETFE	
Cell Efficiency	Up to 23.4%	
Voltage at Max Power(Vmp)	27.6V	
Current at Max Power(Imp)	12.7A	
Open Circuit Voltage(voc)	33V	
Short Circuit Current(Isc)	13.8A	
Operating Temperature	-10°C ~ +65°C	
Best Working Temperature	+25°C	
Folding Number	4	
General		
Weight	29.1lbs / 13.52Kg	
Dimensions	Unfolded	102.8*31.6in / 2612.5*805mm
	Folded	31.6*27.2*1.7in / 805*692*45mm
Warranty		
12 Months		

User Guide

* STC: Irradiation 1000W/m², cell temperature 25°C, atmospheric mass number AM 1.5, measurement tolerance ±3 % (Pm).

Frequently asked questions

Is the solar panel waterproof ?

No. The solar panel is IP65 water-resistant that provides protection against water splash. Please do not leave it in the rain or water for a long time.

What will affect the final conversion efficiency of solar panels ?

The actual solar panel efficiency may be affected by several factors, like weather, sun intensity, shading, panel orientation, temperature, location, dust and dirt. For example, if you live in a place without much sunlight or your panels are covered by shade, you'll get a very low output or none at all.

Is the BLUETTI's solar panel compatible with the third party's power station ?

Yes. Make sure BLUETTI solar panels' voltage is compatible with your power stations' voltage limit, while you're using the same connector. Please feel free to contact us for compatibility with other power stations.

EU REP

Company: POWEROAK GmbH
Address: Lindwurmstr. 114, 80337
München Germany
Mail: logi@bluetti.de

UK REP

Company: POWEROAK ENERGY UK CO.,LTD
Address: Unit 2, NorthGate, Bolsover Business Park,
Woodhouse Lane Chesterfield England S44 6BD
Mail: poweroakeu@bluetti.com



Solarpanel

Benutzerhandbuch


Model: PV350D

Kontaktieren Sie uns:
https://de.bluettipower.eu/
sale-de@bluettipower.com




Benutzerhandbuch


Lieferumfang



Solarpanel






MC4 Kabel






Benutzerhandbuch &
Garantiekarte

Bedienungsanleitung


1 Entfalten



2 Ständer einstellen




3 Anschluss an die Powerstation




MC4-Stecker

Solarladekabel

Multifunktionaler
Verbindungsadapter
(SA2010/S2B
"Luftfahrtstecker" auf XT90)



AC200MAX



Benutzerhandbuch

Hinweis:

Ob in Reihe oder parallel geschaltet, stellen Sie sicher, dass die Gesamtspannung der Solarmodule unter der Eingangsspannungsgrenze der Powerstation liegt.

Achtung

Um die Lebensdauer zu verlängern, sind regelmäßige Inspektionen und Wartungen der Solarpaneele erforderlich.



Nicht
fallen lassen



Nicht
eintauchen



Nicht
biegen



Nicht
einschneiden



Nicht
zerkratzen

Warnung:

Verwenden Sie Solarpaneele nicht bei extremen Wetterbedingungen wie Gewitter, Überschwemmungen, Taifune usw.

Verwenden Sie Solarpaneele immer innerhalb des angegebenen Temperaturbereichs (14-149°F/-10-65°C).

Technische Details

PV350D	
Max. Leistung(Pm)	350W*
Solarzellenlaminierung	ETFE
Solarzellenwirkungsgrad	bis zu 23.4%
Spannung(Max.)	27.6V
Strom(Max.)	12.7A
Leerlaufspannung(Voc)	33V
Kurzschlussstrom(Isc)	13.8A
Betriebstemperatur	-10°C ~ +65°C
Beste Arbeitstemperatur	+25°C
Zahl der Solarmodule	4
Allgemein	
Gewicht	29.1lbs / 13.52Kg
Maße	Entfaltet 87*26.8zoll / 2612.5*805mm
	Gefaltet 26.8*23.1*1.5zoll / 805*692*45mm
Garantie	
12 Monate	

Benutzerhandbuch

* STC: Einstrahlung 1000W/m², Zelltemperatur 25°C, atmosphärische Massenzahl AM 1,5, Messtoleranz ±3 % (Pm).

Wiederkehrende Fragen

Ist das Solarpanel wasserdicht?

Nein. Das Solarpanel ist nach IP65 wasserdicht und bietet Schutz vor Spritzwasser. Bitte lassen Sie es nicht für längere Zeit im Regen oder Wasser liegen.

Wodurch wird die Umwandlungseffizienz von Solarmodulen beeinflusst?

Der tatsächliche Wirkungsgrad des Solarmoduls kann durch mehrere Faktoren wie Wetter, Sonne, Intensität, Schattierung, Panelausrichtung, Temperatur, Standort sowie Staub und Schmutz beeinflusst werden. Wenn Sie z. B. an einem Ort mit wenig Sonnenlicht leben oder Ihre Paneele durch Schatten verdeckt sind, werden Sie nur eine sehr geringe oder gar keine Leistung erhalten.

Ist das BLUETTI Solarpanel mit den Powerstations von Drittanbietern kompatibel?

Ja. Stellen Sie sicher, dass die Spannung des BLUETTI-Solarpanels mit dem Spannungsbereich Ihrer Powerstation kompatibel ist. Beachten Sie die Spannungsgrenzen der Leerlaufspannung. Bitte zögern Sie nicht uns zu kontaktieren wenn Sie weitere Fragen zur Kompatibilität haben.

